



ENERG
енергия · ενεργεια

Y IJA
IE IA

Midea

MGC-V5WD2N8-B



55°C

35°C



A⁺⁺

A⁺⁺⁺



-- dB



60dB

5
6
6
kW

6
6
6
kW



2019

811/2013

Temperature application

Model	For medium - temperature application										
	Energy efficiency class	Unit sound power	average climate			colder climate			warmer climate		
			Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption	Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption	Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption
	-	dB	kW	%	kWh	kW	%	kWh	kW	%	kWh
MGC-V5WD2N8-B	A++	60	6.4	140.7	3655	5.2	113.1	4428	6.2	170.9	1895

Model	For low - temperature application										
	Energy efficiency class	Unit sound power	average climate			colder climate			warmer climate		
			Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption	Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption	Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption
	-	dB	kW	%	kWh	kW	%	kWh	kW	%	kWh
MGC-V5WD2N8-B	A+++	60	6.5	201.8	2631	6.1	173.4	3425	6.2	268.2	1229

Mini Inverter heat pump space heating		Outdoor	MGC-V5WD2N8-B
Outdoor unit sound power (*)	Average climate low temperature application	dB	60
	Average climate medium temperature application	dB	60
Space heating	Energy efficiency class 35°C (Low temp. app.)	-	A+++
Space heating	Energy efficiency class 55°C (Medium temp. app.)	-	A++
Average climate (Design temperature = -10°C)			
Space heating 35°C	Prated (declared heating capacity) @ -10°C	[kW]	6.5
	Seasonal space heating efficiency (η_s)	[%]	201.8
	Annual energy consumption	[kWh]	2,631
Space heating 55°C	Prated (declared heating capacity) @ -10°C	[kW]	6.4
	Seasonal space heating efficiency (η_s)	[%]	140.7
	Annual energy consumption	[kWh]	3,655
Part load conditions space heating average climate low temperature application			
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	5.77
	COPd (declared COP)	-	3.43
	Cdh(degradation coefficient)	-	0.90
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	3.74
	COPd (declared COP)	-	5.04
	Cdh(degradation coefficient)	-	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	2.32
	COPd (declared COP)	-	6.06
	Cdh(degradation coefficient)	-	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	1.87
	COPd (declared COP)	-	9.12
	Cdh(degradation coefficient)	-	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	-10.00
	Pdh (declared heating capacity)	[kW]	6.52
	COPd (declared COP)	-	3.00
	WTOL (Heating water Operation Limit)	[°C]	65

Mini Inverter heat pump space heating		Outdoor	MGC-V5WD2N8-B
(F) Tbivalent temperature	Tblv	[°C]	-7.00
	Pdh (declared heating capacity)	[kW]	5.77
	COPd (declared COP)	-	3.43
Supplementary capacity at P_design	Psup (@Tdesignh: -10°C)	[kW]	0.00
Part load conditions space heating average climate medium temperature application			
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	5.62
	COPd (declared COP)	-	2.36
	Cdh(degradation coefficient)	-	0.90
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	3.52
	COPd (declared COP)	-	3.70
	Cdh(degradation coefficient)	-	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	2.20
	COPd (declared COP)	-	4.21
	Cdh(degradation coefficient)	-	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	1.31
	COPd (declared COP)	-	4.96
	Cdh(degradation coefficient)	-	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	-10.00
	Pdh (declared heating capacity)	[kW]	6.04
	COPd (declared COP)	-	2.02
	WTOL (Heating water Operation Limit)	[°C]	65
(F) Tbivalent temperature	Tblv	[°C]	-7.00
	Pdh (declared heating capacity)	[kW]	5.62
	COPd (declared COP)	-	2.36
Supplementary capacity at P_design	Psup (@Tdesignh: -10°C)	[kW]	0.32
Colder climate (Design temperature = -22°C)			
Space heating 35°C	Prated (declared heating capacity) @ -22°C	[kW]	6.1
	Seasonal space heating efficiency (ηs)	[%]	173.4
	Annual energy consumption	[kWh]	3,425

Mini Inverter heat pump space heating		Outdoor	MGC-V5WD2N8-B
Space heating 55°C	Prated (declared heating capacity) @ -22°C	[kW]	5.2
	Seasonal space heating efficiency (ηs)	[%]	113.1
	Annual energy consumption	[kWh]	4,428
Part load conditions space heating colder climate low temperature application			
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	4.11
	COPd (declared COP)	-	3.76
	Cdh(degradation coefficient)	-	0.90
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	2.38
	COPd (declared COP)	-	5.33
	Cdh(degradation coefficient)	-	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	1.66
	COPd (declared COP)	-	5.78
	Cdh(degradation coefficient)	-	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	1.87
	COPd (declared COP)	-	9.12
	Cdh(degradation coefficient)	-	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	-22.00
	Pdh (declared heating capacity)	[kW]	4.21
	COPd (declared COP)	-	2.12
	WTOL (Heating water Operation Limit)	[°C]	65
(F) Tbivalent temperature	Tbiv	[°C]	-15.00
	Pdh (declared heating capacity)	[kW]	5.00
	COPd (declared COP)	-	3.02
Supplementary capacity at P_design	Psup (@Tdesignh: -22°C)	[kW]	1.92
Part load conditions space heating colder climate medium temperature application			
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	3.21
	COPd (declared COP)	-	2.60
	Cdh(degradation coefficient)	-	0.90

Mini Inverter heat pump space heating		Outdoor	MGC-V5WD2N8-B
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	2.03
	COPd (declared COP)	-	3.18
	Cdh(degradation coefficient)	-	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	1.56
	COPd (declared COP)	-	4.50
	Cdh(degradation coefficient)	-	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	1.44
	COPd (declared COP)	-	5.83
	Cdh(degradation coefficient)	-	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	-22.00
	Pdh (declared heating capacity)	[kW]	3.24
	COPd (declared COP)	-	1.32
	WTOL (Heating water Operation Limit)	[°C]	65
(F) Tbivalent temperature	Tblv	[°C]	-15.00
	Pdh (declared heating capacity)	[kW]	4.25
	COPd (declared COP)	-	2.00
Supplementary capacity at P_design	Psup (@Tdesignh: -22°C)	[kW]	1.98
Warmer climate (Design temperature = 2°C)			
Space heating 35°C	Prated (declared heating capacity) @ 2°C	[kW]	6.2
	Seasonal space heating efficiency (ηs)	[%]	268.2
	Annual energy consumption	[kWh]	1,229
Space heating 55°C	Prated (declared heating capacity) @ 2°C	[kW]	6.2
	Seasonal space heating efficiency (ηs)	[%]	170.9
	Annual energy consumption	[kWh]	1,895
Part load conditions space heating warmer climate low temperature application			
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	5.69
	COPd (declared COP)	-	4.31
	Cdh(degradation coefficient)	-	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	4.01
	COPd (declared COP)	-	6.39
	Cdh(degradation coefficient)	-	0.90

Mini Inverter heat pump space heating		Outdoor	MGC-V5WD2N8-B
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	2.07
	COPd (declared COP)	-	8.71
	Cdh(degradation coefficient)	-	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	2.00
	Pdh (declared heating capacity)	[kW]	5.69
	COPd (declared COP)	-	4.31
	WTOL (Heating water Operation Limit)	[°C]	65
(F) Tbivalent temperature	Tblv	[°C]	7.00
	Pdh (declared heating capacity)	[kW]	4.01
	COPd (declared COP)	-	6.39
Supplementary capacity at P_design	Psup (@Tdesignh: 2°C)	[kW]	0.55
Part load conditions space heating warmer climate medium temperature application			
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	6.17
	COPd (declared COP)	-	2.77
	Cdh(degradation coefficient)	-	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	3.97
	COPd (declared COP)	-	3.90
	Cdh(degradation coefficient)	-	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	2.06
	COPd (declared COP)	-	5.28
	Cdh(degradation coefficient)	-	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	2.00
	Pdh (declared heating capacity)	[kW]	6.17
	COPd (declared COP)	-	2.77
	WTOL (Heating water Operation Limit)	[°C]	65
(F) Tbivalent temperature	Tblv	[°C]	7.00
	Pdh (declared heating capacity)	[kW]	3.97
	COPd (declared COP)	-	3.90
Supplementary capacity at P_design	Psup (@Tdesignh: 2°C)	[kW]	0.00

Mini Inverter heat pump space heating		Outdoor	MGC-V5WD2N8-B
Product description	Air-to-water heat pump	Y/N	Yes
	Water-to-water heat pump	Y/N	No
	Brine-to-water heat pump	Y/N	No
	Low-temperature heat pump	Y/N	No
	Equipped with a supplementary heater	Y/N	Yes
	Heat pump combination heater	Y/N	Yes
Air to water unit	Rated airflow (outdoor)	[m ³ /h]	3900
Brine/water to water unit	Rated water/brine flow (outdoor H/E)		/
Other	Capacity control	-	Inverter
	Poff (Power consumption Off mode)	[kW]	0.013
	Pto (Power consumption Thermostat off mode)	[kW]	0.020
	Psb (Power consumption Standby mode)	[kW]	0.013
	PCK (Power crankcase heater model)	[kW]	0.000
	Qelec (Daily electricity consumption)	[kWh]	/
	Qfuel (Daily fuel consumption)	[kWh]	/
<p>Note :</p> <p>Product fiche data according to energy label directive 2010/30/EC regulation (EU) 811/2013.</p> <p>Sound power measured according to the EN12102 under conditions of the EN14825.</p> <p>Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.</p>			

Mini Inverter heat pump space cooling		Outdoor	MGC-V5WD2N8-B
Outdoor unit sound power (*)	Average climate low temperature application	dB	62
	Average climate medium temperature application	dB	62
Space cooling 7°C	Prated (declared cooling capacity) @ 35°C	[kW]	5.6
	Seasonal space cooling efficiency (η_s)	[%]	200.43
	Annual energy consumption	[kWh]	658
Space cooling 18°C	Prated (declared cooling capacity) @ 35°C	[kW]	6.9
	Seasonal space cooling efficiency (η_s)	[%]	309.5
	Annual energy consumption	[kWh]	527
Part load conditions space cooling : low temperature application@7°C			
(A) condition (35°C)	Pdc (declared cooling capacity)	[kW]	5.58
	EERd (declared EER)	-	3.38
	Cdc(degradation coefficient)	-	0.90
(B) condition (30°C)	Pdc (declared cooling capacity)	[kW]	4.27
	EERd (declared EER)	-	4.52
	Cdc(degradation coefficient)	-	0.90
(C) condition (25°C)	Pdc (declared cooling capacity)	[kW]	2.90
	EERd (declared EER)	-	5.46
	Cdc(degradation coefficient)	-	0.90
(D) condition (20°C)	Pdc (declared cooling capacity)	[kW]	1.33
	EERd (declared EER)	-	6.91
	Cdc(degradation coefficient)	-	0.90

Mini Inverter heat pump space cooling		Outdoor	MGC-V5WD2N8-B
Part load conditions space cooling : medium temperature application@18°C			
(A) condition (35°C)	Pdc (declared cooling capacity)	[kW]	6.86
	EERd (declared EER)	-	5.29
	Cdc(degradation coefficient)	-	0.90
(B) condition (30°C)	Pdc (declared cooling capacity)	[kW]	5.27
	EERd (declared EER)	-	7.03
	Cdc(degradation coefficient)	-	0.90
(C) condition (25°C)	Pdc (declared cooling capacity)	[kW]	3.32
	EERd (declared EER)	-	8.14
	Cdc(degradation coefficient)	-	0.90
(D) condition (20°C)	Pdc (declared cooling capacity)	[kW]	1.61
	EERd (declared EER)	-	11.31
	Cdc(degradation coefficient)	-	0.90
Air to water unit	Rated airflow (outdoor)	[m ³ /h]	3900
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	-	/
Other	Capacity control	-	Inverter
	Poff (Power consumption Off mode)	[kW]	0.013
	Pto (Power consumption Thermostat off mode)	[kW]	0.005
	Psb (Power consumption Standby mode)	[kW]	0.013
	Pck (Power crankcase heater mode)	[kW]	0.000
	Qelec (Daily electricity consumption)	[kWh]	/
	Qfuel (Daily fuel consumption)	[kWh]	/

Outdoor unit	Ambient Temperature: 35/24 Water temperature: 23/18			Ambient Temperature: 35/24 Water temperature: 12/7			Ambient Temperature: 7/6 Water temperature: 30/35			Ambient Temperature: 2/1 Water temperature: 30/35		
	Capacity kW	Power input kW	EER	Capacity kW	Power input kW	EER	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP
MGC-V5WD2N8-B	6.50	1.275	5.10	5.50	1.692	3.25	6.50	1.226	5.30	5.60	1.333	4.20

Outdoor unit	Ambient Temperature: -7/-8 Water temperature: 30/35			Ambient Temperature: 7/6 Water temperature: 40/45			Ambient Temperature: 2/1 Water temperature: 40/45			Ambient Temperature: -7/-8 Water temperature: 40/45		
	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP
MGC-V5WD2N8-B	6.20	1.938	3.20	6.60	1.650	4.00	6.50	2.063	3.15	6.10	2.346	2.60

Outdoor unit	Ambient Temperature: 7/6 Water temperature: 47/55			Ambient Temperature: 2/1 Water temperature: 47/55			Ambient Temperature: -7/-8 Water temperature: 47/55		
	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP
MGC-V5WD2N8-B	6.30	1.969	3.20	6.30	2.250	2.80	5.70	2.651	2.15